

# SAVANT PRO AUDIO 4

Press Play on A Scalable, All-In-One Audio Solution



## SAVANT

savant.com

© 2016 Savant Systems, LLC. All rights reserved.

## KEY FEATURES

---

### THE TOTAL AUDIO PACKAGE

A true all-in-one experience, the Pro Audio 4 features built-in streaming, distribution, and amplification for complete audio immersion.

### MUSIC IN EVERY ROOM

The Pro Audio 4 provides four zones of high-quality audio that syncs automatically between rooms, so you never miss a note. Play it all, straight from the Savant Pro App or your Pro Remote.

### STREAM FREELY

The Pro Audio 4 includes a single stream of Savant Music, with support for an additional stream through the Savant Smart Host, so you can personalize the music in any room.

### EXPAND YOUR REACH

Connect up to three Pro Audio 4 units to get twelve distinct audio zones and three Savant Music streams, and add even more rooms to your musical range.

### AUDIOPHILE APPROVED

Your music comes in with perfect clarity. The high-quality 50 watt amplifier, with integrated audio processing, gives you four stereo zones of unmatched, immersive fidelity.

### EASY INSTALLATION

With rack, structured media, and credenza mounting options, the Pro Audio 4 can adapt to most spaces, making it simple to install anywhere.

## SPECIFICATIONS

---

### ENVIRONMENTAL

---

Temperature 32° to 104° F (0° to 40° C)

Humidity 10% to 80% (non-condensing)

Maximum BTU 750 BTU/HR

### POWER

---

Input Power 100/240V AC (50/60 Hz) 2.7A

Maximum Power 225W

### COMPLIANCE

---

Safety and Emissions FCC Part 15B | CE Mark | UL | C-Tick

RoHS Compliant

### MINIMUM SUPPORTED RELEASE

---

Savant OS: da Vinci 8.2

Requires pairing with a Savant Smart Host or Pro Host

### CONTROL PORTS

---

4 IR ports

2 RS-232 ports

### DIMENSIONS

---

Height 3.03 in (7.7 cm)

Width 12 in (30.5 cm)

Depth 14.17 in (36.0 cm)

Weight 10.6 lb (4.81 kg)

Rack Space 2U

### OPERATING PARAMETERS

---

Rated Power (Speaker Output) 50 WPC at 8 ohms (THD+N < 0.1%)  
70 WPC at 8 ohms (THD+N < 1.0%)

Frequency Response 20 Hz - 20 kHz +/- 0.5 dB, speaker output

Signal-to-Noise Ratio (SNR) >95 dB, speaker output

Supported Digital Input Formats 44.1 kHz / 48 kHz / 96 kHz at 16-bit / 20-bit / 24-bit resolution

### SCALABILITY

---

Connect up to 3 units using AVB compliant switching

Enable 18 zones of distributed audio (12 amplified, 6 pre-amp)

Includes 2 additional line level output zones

# SAVANT

savant.com

© 2016 Savant Systems, LLC. All rights reserved.